

For best results, use Elephant Armor® Tools & Accessories



9" (230mm) and 18" (450mm)
Smooth Roller



9" (230mm), 9.5" (240mm) and 18" (450mm)
Textured Roller



Expandable Aluminum Roller Frame
(rollers not included)



Showing Expandable Roller Frame at 9" to 18"
with 1/4" and 1/2" depth gauges (sold separately)



1/4" and 1/2" Roller Depth Gauges
for 9", 9.5" and 18" rollers



Aluminum Roller
with 1/4", 1/2" and 3/4" Depth Gauges
(sold separately)



Elephant Armor® Cure provides an effective curing membrane that will dry to a clear (non-yellowing) membrane.



Elephant Armor® Primer a high solids, acrylic polymer latex bonding agent specifically designed to be used with Elephant Armor® on any concrete or asphalt surface.



Elephant Armor® Overlay Primer is a ready to use, rewettable polyvinyl acetate bonding agent, which bonds Elephant Armor® mortars to properly prepared concrete, and between Elephant Armor® lifts. It can also be used to bond to wood and EPS foam.



Elephant Armor® Delay to increase working time.
(comes with measuring scoop)



GST 2 Gallon Pump-up Sprayer for application of Elephant Armor® Cure and Primer



GST Sprayer Tips for GST 2 gallon pump-up sprayer