



STRUCTUREBOND™ Gun Cleaner

(70975915 / 500 ml)

UPDATE

June 13, 2018

Make sure that you have an up-to-date technical data sheet in hand by consulting our website: techniseal.com
U.S.A. and Canada: dial 1 800 465-7325
Others: dial (514) 523-8324 (Canada)

APPLICATIONS

- StructureBond Gun
- Any acid-resistant surface

DESCRIPTION

Cleans StructureBond application gun and removes fresh, non-cured polyurethane foam adhesive.

DIRECTIONS

BEFORE YOU BEGIN

Before using this cleaner, make sure you have an up-to-date technical data sheet in hand by visiting techniseal.com.
ALWAYS TEST on a small hidden area to ensure compatibility before use.

Necessary tools:

- Spray nozzle

APPLICATION

CAUTION: Always wear eye protection, gloves and protective clothing. Use in a well-ventilated area. **Do not** smoke while using and **do not** use near an open flame.

To clean application gun:

1. Remove empty adhesive canister.
2. Screw on cleaner canister and pull trigger a few times to fill gun.
3. Allow cleaner to remain in the gun for approximately 15 minutes.
4. Pull trigger until cleaner comes out clear.
5. Remove cleaner canister from the gun.
6. Clean and dry screw thread on the canister.

To remove non-cured adhesive:

1. Attach a spray nozzle to the cleaner canister.
2. Press nozzle with finger and spray cleaner on the area to be cleaned.
3. Remove nozzle when finished.

WARNING: Dispense into a suitable container. Cleaner may damage some materials. **Always** test on scrap material prior to use.

STORAGE AND DISPOSAL

Do not puncture, incinerate or store above 38°C. Protect from sunlight. Store can upright to avoid obstruction of the valve. Store in a well-ventilated place. Store locked up. Dispose of contents in accordance with local regulations.

SAFETY WARNINGS

KEEP OUT OF THE REACH OF CHILDREN. Keep away from heat, sparks and flame. Keep away from flames, such as a pilot light, and any object that sparks, such as an electric motor. Do not puncture or incinerate container. Do not expose to heat or store at temperatures above 120°F. Use only with adequate ventilation. Do not breathe vapor or mist. Do not swallow. Avoid contact with eyes. Keep container tightly closed and sealed until ready for use. Wash thoroughly after handling.

SHIPPING

LAND:

Transported in limited quantity; DOT-2P

SEA:

UN1950; Aerosols; Class : 2.1; DOT-2P

PACKAGING

Product Code	Color	Size	Units per box	Boxes per pallet
70975915	N/A	500ml	12	120

LIMITED WARRANTY

Manufacturer's liability is limited to the replacement of the product. A proof of purchase will be required for any claim.